



MAXAM MS910R

MULTIPURPOSE RADIAL

For use in loader, earthmover and agricultural applications where high traction is required.

- Versatile non-directional, off-the-road tread pattern
- Excellent on-road suitability
- All-steel radial construction for maximum durability, stability, traction and comfort
- Special self-cleaning design with dome mud breakers

Applications:



Multipurpose Radial

Size	Type	Rim	O.D.		S.W.		T.D.		Speed		Infl. P.		L.C.C.		L.I.
			in	mm	in	mm	32nds	mm	mph	kph	psi	KPa	lbs	kg	
335/80R18 MPT	TL	11.00	38.9	989	13.1	334	23	18.5	68	110	51	350	4400	2000	132K
			41	1041	13.1	334	23	18.5	68	110	94	650	7150	3250	
335/80R20 MPT	TL	11.00	41	1041	13.1	334	23	18.5	68	110	94	650	7150	3250	149K
			41	1041	13.1	334	23	18.5	68	110	94	650	7150	3250	





Construction Applications

Size	Type	Rim	O.D.	S.W.	T.D.	Speed	Infl. P.	L.C.C.	L.I.
			in mm	in mm	32nds mm	mph kph	psi KPa	lbs kg	
335/80R18 EM	TL	11.00	38.9	13.1	23	6	54	6400	145A2
			989	334	18.5	10	375	2900	
365/70R18 EM	TL	11.00	38	14.3	26	6	54	6600	146A2
			966	363	20.5	10	375	3000	
405/70R18 EM	TL	13.00	40	15.9	26	6	54	8050	153A2
			1023	405	20.5	10	375	3650	
335/80R20 EM	TL	11.00	41	13.1	23	6	54	6800	147A2
			1041	334	18.5	10	375	3075	
365/80R20 EM	TL	11.00	42.9	14.3	23	6	54	8050	153A2
			1089	363	18.5	10	375	3650	
405/70R20 EM	TL	13.00	42.4	16.0	26	6	54	8550	155A2
			1076	407	20.5	10	375	3875	
405/70R24 EM	TL	13.00	46.5	16.1	26	6	54	9350	158A2
			1181	409	20.5	10	375	4250	

Industrial Applications

Size	Type	Rim	O.D.	S.W.	T.D.	Speed	Infl. P.	L.C.C.	L.I.
			in mm	in mm	32nds mm	mph kph	psi KPa	lbs kg	
340/80R18 IND	TL	11.00	38.9	13.1	23	30	54	6000	143A8/B
			989	334	18.5	50	375	2725	
400/70R18 IND	TL	13.00	40	15.9	26	30	54	6800	147A8/B
			1023	405	20.5	50	375	3075	
460/70R24 IND	TL	14.00	49.2	18.1	30	30	54	9650	159A8/B
			1249	460	23.5	50	375	4375	

