



MAXAM MS930

LOGXTRA - LS2 FORESTRY

Designed for use on demanding forestry equipment. High strength, belt-stabilized tire construction provides excellent traction and flotation in severe logging applications.

- Heavy duty shoulder and sidewall
- Maximum protection from cuts, impacts and punctures
- Cut resistant compound specifically engineered for forestry service
- Steel reinforced undertread
- Extra wide footprint provides exceptional flotation in muddy and wet ground conditions
- Nylon-wrapped beads prevent unwinding

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5mph 10kph	
28L-26	16	TL	DW25B	64.7 1644	28.1 714	72 57	35 240	14800 6700	174A2 / 162A6
	20	TL	DW25B	64.2 1632	27.9 709	72 57	40 275	16100 7300	177A2 / 165A6
	26	TL	DW25B	64.7 1644	28.1 714	72 57	55 380	20400 9250	185A2 / 173A6
24.5-32	20	TL	DH21	72.1 1831	24.5 622	76 60	45 310	18700 8500	182A2 / 170A6
30.5L-32	20	TL	DH27	72.7 1847	30.5 775	76 60	35 240	18700 8500	182A2 / 170A6
	26	TL	DH27	72.7 1847	30.2 768	76 60	45 310	22000 10000	188A2 / 176A6
	32	TL	DH27	72.7 1847	30.2 775	76 60	55 380	24700 11200	192A2 / 180A6
35.5L-32	26	TL	DH31	79.3 2016	35.2 895	79 63	40 275	26800 12150	195A2 / 183A6
	30	TL	DH31	79.2 2011	35.5 902	79 63	45 310	29100 13200	198A2 / 186A6

