



MAXAM MS931

LOGXTRA - LS2 FORESTRY

Designed for use on demanding forestry equipment. High strength, belt stabilized tire construction provides excellent traction and flotation in severe logging applications.

- Heavy duty shoulder and sidewall
- Maximum protection from cuts, impacts and punctures
- Cut resistant compound specifically engineered for forestry service
- Steel reinforced undertread
- Extra wide footprint provides exceptional flotation in muddy and wet ground conditions
- Nylon-wrapped beads prevent unwinding

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C.	L.I.
				in	in	32nds	psi	(lbs/kg)	
				mm	mm	mm	KPa	5 mph	
								10 kph	
23.1-26	16	TL	DW20B	63.8	22.8	72	40	13900	172A2 /
				1620	580	58	275	6300	160A6
28L-26	16	TL	DW25B	63.9	28.0	76	35	14800	174A2 /
				1624	710	60	240	6700	162A6
	20	TL	DW25B	64.1	27.8	76	40	16100	177A2 /
				1628	707	60	275	7300	165A6
26	TL	DW25B	64.1	27.8	76	55	20400	185A2 /	
			1628	707	60	380	9250	173A6	
24.5-32	20	TL	DH21	72.1	24.5	75	45	18700	182A2 /
				1831	622	60	310	8500	170A6
30.5L-32	20	TL	DH27	73.0	30.3	82	35	18700	182A2 /
				1855	769	65	240	8500	170A6
	26	TL	DH27	73.0	30.2	82	45	22000	188A2 /
				1855	768	65	310	10000	176A6
32	TL	DH27	73.0	30.2	82	55	24700	192A2 /	
			1855	768	65	380	11200	180A6	
35.5L-32	26	TL	DH31	79.2	35.5	84	40	26800	195A2 /
				2011	902	67	275	12150	183A6
	30	TL	DH31	79.2	35.5	84	45	29100	198A2 /
				2011	902	67	310	13200	186A6

