

AGRIXTRA H

- Super volume R1W Tires optimized for improved flotation and heavy loads up to 40 mph - D Rated
- Designed for both Harvester and Floater (Spreader) applications



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
620/75R26	166A8/B TL	505	60	360
750/50R26	169A8/166D TL	425	48	346
750/65R26	169A8/166D TL	529	60	419
650/75R32	175A8/172D TL	690	73	427
800/65R32	181A8/178D TL	690	73	509
900/60R32	184A8/ 181D TL	772	72	560
1000/50R25	175A8/170D TL	849	72	499
1050/50R32	178A8/170D TL	1006	76	733
1250/50R32	194A8/191B TL	1255	81	870

FLOTXTRA

- Radial steel constructed implement tires optimized for high loads and speeds up to 40 mph (70 kph) - D Rated
- Designed for both transportation or forage equipment
- High durability, long tread life and improved lateral stability



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
500/60R22.5	155D TL	258	24	210
560/45R22.5	152D TL	212	24	193
560/60R22.5	161D TL	298	24	251
600/50R22.5	159D TL	286	24	237
710/40R22.5	161D TL	321	24	251
600/55R26.5	165D TL	353	25	279
650/55R26.5	169D TL	381	25	315
710/50R26.5	170D TL	435	25	326
800/45R26.5	174D TL	481	25	364
650/65R30.5	176D TL	534	29	385
710/50R30.5	173D TL	497	29	353
750/60R30.5	181D TL	603	29	448
605/70R20.5	176F TL	603	23	261



MAXAM

MAXAM TIRE INTERNATIONAL

300 Rosewood Drive, Suite 102, Danvers, MA 01923 U.S.A.
T. 844-MAXAM-NA F. 978-560-0624 - MAXAMTIRE.COM

RADIAL AG LIMITED WARRANTY

The below Limited Warranty and Adjustment Policy is a commitment of tire replacement under certain specified conditions as provided below: This Warranty Policy applies to all MAXAM radial agricultural tires as specified below and does not require the existence of a defect to be considered eligible for an adjustment.

Agricultural Use*	Stubble Damage or Field Hazard Coverage	Scraper Application Use*
Up to Eight Years	With Stubble Prevention Device	With Appropriate Weight & Air Pressure Settings
Year 1 100%*	Year 1 80%	Year 1 80%
Year 2 100%*	Year 2 60%	Year 2 60%
Year 3 80%	Year 3 40%	Year 3 40%
Year 4 70%	Year 4 20%	Year 4 20%
Year 5 60%	Year 5 No Coverage	Year 5 No Coverage
Year 6 50%	Year 6 No Coverage	Year 6 No Coverage
Year 7 30%	Year 7 No Coverage	Year 7 No Coverage
Year 8 20%	Year 8 No Coverage	Year 8 No Coverage

* 100% FREE REPLACEMENT

See warranty document for policy details & conditions

PRODUCT ELIGIBILITY

All MAXAM Brand Radial Agriculture Tires Manufactured and/or sold after January 1, 2018, and distributed by MAXAM Tire per it's identification code and production date. This policy applies to either the Original Owner, the User of the Tires, or the Original Purchaser of the agricultural equipment mounted with the tires. The MAXAM Agricultural Tires covered by this warranty policy belong to the following family of Radial Products: AgriXtra85, AgriXtra70, AgriXtra65, AgriXtra XL, AgriXtra H, AgriXtra N & FloTextra.

For complete details on the MAXAM Radial Ag Limited Warranty the document is available on our website: www.maxamtire.com or contact us at 1-844-MAXAM-NA

BUSINESS SOLUTIONS PROVIDER

V9.19

MAXAM



RADIAL AGRICULTURAL TIRES

MAXAMTIRE.COM

AGRIXTRA 85

- Standard Sized R1W Tires for varied farming operations
- Designed for Ag machinery applications from Tractors to Harvesters



SIZE	SIZE	L.I.	WT.	T.D.	GFP
Metric	U.S. Equiv.		lbs.	32nds	sq. in.
250/85R24	9.5R24	109A8/B TL	86	48	109
280/85R24	11.2R24	115A8/B TL	99	50	128
320/85R24	12.4R24	122A8/B TL	124	52	158
340/85R24	13.6R24	125A8/B TL	137	53	174
380/85R24	14.9R24	131A8/B TL	169	54	206
420/85R24	16.9R24	137A8/B TL	203	58	243
280/85R28	11.2R28	118A8/B TL	114	50	139
320/85R28	12.4R28	124A8/B TL	134	52	169
340/85R28	13.6R28	127A8/B TL	150	53	185
380/85R28	14.9R28	133A8/B TL	184	54	217
420/85R28	16.9R28	146A8/B TL	221	58	256
380/85R30	14.9R30	135A8/B TL	200	54	230
420/85R30	16.9R30	140A8/B TL	236	63	264
460/85R30	18.4R30	145A8 TL	271	64	306
320/85R32	12.4R32	126A8/B TL	150	63	179
380/85R34	14.9R34	146A8/B TL	212	64	237
420/85R34	16.9R34	142A8/B TL	260	63	280
460/85R34	18.4R30	147A8/B TL	300	64	325
320/85R36	12.4R36	128A8/B TL	163	52	190
340/85R36	13.6R36	132A8/B TL	192	58	211
340/85R38	13.6R38	133A8/B TL	198	58	217
380/80R38	14.9R38	146A8/B TL	212	57	210
420/85R38	16.9R38	144A8/B TL	280	63	295
460/85R38	18.4R38	149A8/B TL	326	64	343
520/85R38	20.8R38	155A8/B TL	404	67	409
460/85R42	18.4R42	156A8/B TL	399	64	422
480/80R42	18.4R42	151A8 TL	373	64	364
520/85R42	20.8R42	157A8/B TL	448	69	435
480/80R46	18.4R46	158A8/B TL	417	64	336
520/85R46	20.8R46	158A8/B TL	496	69	449
480/80R50	18.4R50	176A8/B TL	518	64	346

AGRIXTRA 70

- Premium R1W Traction Tire designed for wide tread field applications
- Designed to carry the same load capacity at both 25 & 30 mph



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
360/70R24	122A8/B TL	139	50	158
380/70R24	125A8/B TL	156	52	174
420/70R24	130A8/B TL	182	53	201
480/70R24	141A8/138D TL	182	55	249
360/70R28	125A8 TL	148	50	174
380/70R28	127A8/B TL	170	52	185
420/70R28	133A8/B TL	198	53	217
480/70R28	140A8/B TL	249	55	264
480/70R30	155A8/152D TL	265	60	272
520/70R30	145A8 TL	304	63	306
480/70R34	155A8/B TL	288	60	288
520/70R34	148A TL	332	63	332
480/70R38	145A8 TL	319	57	306
520/70R38	150A8/B TL	366	63	354
580/70R38	155A8/B TL	444	71	409
620/70R42	169A8/ 166D TL	512	73	419

AGRIXTRA XL

- Large Volume R1W Tires for High Horsepower Tractors and Harvesters
- Designed to operate in the field, on the road, and in scraping applications



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
600/65R28	157A8/154D TL	354	64	297
600/70R30	161A8/ 158D TL	397	64	336
650/85R38	176A8/173D TL	739	78	514
710/70R38	174A8/171D TL	691	78	487
710/70R42	176A8/173D TL	754	78	514
800/70R38	176A8/178D TL	690	78	594

AGRIXTRA 65

- Premium R1W Traction Tire designed for wide tread field applications
- Designed for Low Pressure operations to reduce soil compaction.



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
440/65R24	131A8/128D TL	173	53	190
480/65R24	136A8/133D TL	199	54	217
540/65R24	143A8/140D TL	247	58	264
420/65R28	131A8/128D TL	174	52	190
440/65R28	134A8/131D TL	193	53	206
480/65R28	139A8/136D TL	219	54	236
540/65R28	145A8/142D TL	279	58	280
540/65R30	153A8/150D TL	304	63	265
540/65R34	148A8/145D TL	329	64	306
540/65R38	150A8/147D TL	364	64	325
600/65R38	156A8/153D TL	400	66	385
650/65R38	160A8/157D TL	492	71	435
650/65R42	161A8/158D TL	526	73	449

AGRIXTRA N

- R1W & R1 Narrow Tires optimized for both field and road applications
- Designed for High Clearance or Narrow Crop Applications
- Suitable for both Tractors and Self-Propelled Sprayers



SIZE	L.I.	WT.	T.D.	GFP
Metric		lbs.	32nds	sq. in.
420/90R30	147A8/B TL	254	62	243
380/90R46	159A8/B TL	298	58	237
380/90R50	160A8/B TL	342	58	244
380/90R54	152A8/B TL	262	58	323
VF380/90R46	173D TL	342	58	321
VF380/105R50	176D TL	418	49	258