



MAXAM

MS915

GRADER - TELEHANDLER

Deep, non-directional traction pattern for telehandler and grader use.

- Excellent traction in all off-road conditions
- Thick undertread for improved puncture resistance
- Wear and cut resistant tread compound
- Wide, flat footprint profile for maximum stability and wear
- Increased net-to-gross and tread depth for highest tread life

Applications:



Size	P.R.	Type	Rim	Alt. Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
					in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	25 mph 40 kph	
13.00-24	12	TL	10.00VA	8.00TG	50.3	13.1	32	65	12300	44	6000	168A2/143A8
					1278	333	25	450	5600	300	2725	
	16		10.00VA	-	50.3	13.1	32	87	14300	58	7150	173A2/149A8
					1278	333	25	600	6500	400	3250	
14.00-24	12	TL	10.00VA	8.00TG	53.1	14.3	34	62	13900	36	6800	172A2/147A8
					1349	363	27	425	6300	250	3075	
	16		10.00VA	-	53.1	14.3	34	80	16100	51	8050	177A2/153A8
					1349	363	27	550	7300	350	3650	

