



MAXAM MS402

E4

For use in higher speed applications on well-maintained haul roads.

- Excellent traction on maintained haul roads
- Solid tread centerline minimizes vibration and increases tread life
- Wide, square footprint distributes load to minimize haul road disturbance
- Reinforced bead, shoulder and sidewall for increased cut resistance
- Heat resistant undertread reduces tire temperature
- Multiple tread compound options target specific site requirements

Applications:



Size	Rating	Type	Rim	O.D.	S.W.	T.D.	Tread Compound	TMPH/ TKPH	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm			psi KPa	30 mph 50 kph	
18.00R33	★★	TL	13.00/2.5	73.8	20.1	66	Standard	145/212	102	24000	191B
				1874	511	52	Cut Resistant	116/169	700	10900	
24.00R35	★★	TL	17.00/3.5	86.5	27.8	71	Standard	266/330	102	40800	209B
				2196	705	56	Cut Resistant	182/265	700	18500	
27.00R49	★★	TL	19.50/4.0	106.4	29.0	82	Standard	337/492	102	60000	223B
							Ultra Cut Resistant	233/340			
				2702	737	65	Cut Resistant	291/495	700	27250	
30.00R51	★★	TL	22.00/4.5	114.4	33.7	93	Standard	401/585	102	74000	230B
							Ultra Cut Resistant	271/395			
				2906	856	74	Cut Resistant	329/480	700	33500	
							Heat Resistant	477/695			

