



# MAXAM MS912

**BIAS E2/G2/L2**

Aggressive R4 pattern designed to maximize traction in soft underfoot conditions. Ideal for use on graders, loaders and earthmovers.

- Heavy duty bias construction maximizes traction and flotation
- Wear and cut resistant tread compound
- Self-cleaning tread design

Applications:



Size	P.R.	Type	Rim	O.D.	S.W.	T.D.	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	Infl. P.	L.C.C. (lbs/kg)	L.I.
				in mm	in mm	32nds mm	psi KPa	5 mph 10 kph	psi KPa	30 mph 50 kph	psi KPa	25 mph 40 kph	
15.5-25	12	TL	12.00/1.3	50.2	15.5	30	58	12300	36	7150	36	5840	149B/142A8/ 168A2
				1276	394	24	400	5600	250	3250	250	2650	
17.5-25	12	TL	14.00/1.5	53.1	17.3	31	51	13600	33	8050	29	6400	153B/145A8/ 171A2
				1350	439	25	350	6150	225	3650	200	2900	
	16			53.1	17.3	31	69	16100	44	9350	40	7400	158B/150A8/ 177A2
				1350	439	25	475	7300	300	4250	275	3350	
20.5-25	12	TL	17.00/2.0	58.3	20.9	35	36	14800	29	9900	25	7850	160B/152A8/ 174A2
				1482	530	28	250	6700	200	4500	175	3550	
	16			58.3	20.9	35	51	18200	40	12000	32	8800	167B/156A8/ 181A2
				1482	530	28	350	8250	275	5450	225	4000	

